

MATERIAL SAFETY DATA SHEET

PRODUCT : GREASIL 4000

DESCRIPTION: SILICONE GREASE

PROPERTIES:

Physical Form - Paste/grease

Colour - Colourless

Odour - Odorless

S.G @ 15°C - 1.00

Flash Point °C - 320

Ph (Neat Product) - N/A

Ph (Various % Solution) - N/A

Shelf Life - Indefinite

Packaging Details - Plastic Containers

Hazard Warning Label - None required

Worked Penetration - 200-260

Unworked Penetration - 180-200

Spill and disposal Procedure - Scrape up paste. Place all waste into suitable containers for disposal at an approved site in accordance with local regulations.

Extinguishing Media in Case of Fire - Carbon dioxide, dry chemical or foam

Details of Hazardous Components - This product does not contain any hazardous components

Conditions to Avoid - Avoid contact with strong oxidizing agents

Protection of Personnel - The use of goggles is recommended where there is a risk of accidental eye contact.

Effects of Contact - Eyes - May cause irritation
Skin - None

First Aid Procedures - Eyes - Irrigate eye with copious quantities of fresh water for at least 15 minutes.
If irritation persists seek medical attention.
Skin - Wash affected area with soap and water.
Irritation should not occur but if irritation occurs seek medical advice.

Ingestion - Give water to drink. DO NOT induce vomiting although casualty may be allowed to vomit naturally.
If any signs of discomfort seek medical attention.

Inhalation - Not applicable