REMS Mini-Press ACC

Universal, super handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. Li-lon technology. For battery and corded operation.

Pipe pressing joints	Ø 10-40 mm	
Complete range of REMS pressing tongs Mini for all		
common pressfitting systems, see page 108–118.		

REMS Mini-Press ACC Li-lon – universal up to Ø 40 mm. Super light, super small, super handy. With automatic circuit control. Secure crimping in seconds. Automatic locking of the pressing tongs.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini for all common pressfitting systems (page 108–118). High-compression pressing tongs in forged and specially hardened steel. Pressing contours of REMS pressing tongs are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing.

Execution

Super light, super small, super handy. Drive unit with battery only 2.4 kg. Drive unit with pressing tongs under 34 cm. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Ergonomically designed housing. Swivelling pressing tongs seat. Secure seating of pressing tongs by automatic locking. For battery and corded operation. Electronic charging status check with flat battery protection and charging status indicator with 2-coloured LED

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Powerful electro-hydraulic drive with powerful battery motor 14,4 V, 420 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Battery Li-Ion 14.4 V with 1.65, 2.2 or 3.5 Ah capacity. Powerful and light. 20% faster and 30 % lighter than Ni-Cd 12 V. Height energy density for approx. 50 % more pressings than Ni-Cd 12 V. Li-Ion 14.4 V, 3.5 Ah battery for approx. 370 pressings Viega Profipress DN 15 per battery charge. Overheating and overloading protection by temperature monitor (NTC). Rapid charger for short charging times. No memory effect for maximum battery performance. Voltage supply Li-Ion 230 V for mains operation instead of battery Li-Ion 14.4 V, as accessory.

Confirmation of suitability

See page 139.

Hold-Harmless and Indemnification Agreement See page 140.

Supply format

REMS Mini-Press ACC Li-Ion Basic-Pack. Cordless radial press with automatic circuit control for producing pipe pressing joints Ø 10–40 mm. For operating with REMS pressing tongs Mini. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 14,4 V, 420 W, obust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, Safety tip switch. Battery Li-Ion 14,4 V, 1,65 Ah, rapid charger Li-Ion/Ni-Cd 230 V or 110 V, 50–60 Hz, 65 W. In sturdy steel case.

ArtNo.	
578012	

Other voltages on request.

Accessories

Description	ArtNo.	
REMS pressing tongs Mini see page 108-118.		
REMS cropping tongs Mini for threaded rods see page	119.	
REMS Mini-Press ACC Li-lon drive unit, without battery	578001	
Battery Li-Ion 14.4 V, 1.65 Ah	571545	
Battery Li-Ion 14.4 V, 2.2 Ah	571550	
Battery Li-Ion 14.4 V, 3.5 Ah	571555	
Rapid charger Li-Ion/Ni-Cd 230 V, 50-60 Hz, 65 W	571560	
Voltage supply Li-Ion 230 V for mains operation instead of battery Li-Ion 14.4 V.	571565	
Steel case with inlay	578290	



< 34 cm

German Quality Product



