


DSV531460

Caleffi 531 Series Safety Valve 15mm x 20mm
600kPa



Technical Specification

15mm inlet 20mm Outlet, 600kPa
 Housing: Brass EN 12165 CW617N
 Top part: Brass EN 12165 CW617N
 Control spindle: Brass EN 12164 CW614N
 Spindle seal: EPDM
 Diaphragm: EPDM
 Spring: Steel EN 12270-1
 Knob: ABS
 Operating medium: Water
 Rated pressure: PN 10
 Working temperature range: 5–110°C



	5315..	5314.
A	3/4"	1/2"
B	1"	3/4"
C	30	24
D	82	72
E	40,5	33,5



Application

The Caleffi 531 Series Safety Valve 15mm x 20mm 600kPa is used in plumbing systems to provide a safety function and is installed mostly in plant rooms.

Warranty

[Download the latest warranty statement](#)

Features

- Fail-safe Valve performance is ensured even in the case of diaphragm wear or breakage.
- Discharge over pressure 20%.
- Closing pressure 20%. It allows minimization of damage due to water leakage in the case of accidental opening of the valve.
- Maximum working temperature: 100°C
- Factory set: 6 bar
- Increased outlet diameter. This characteristic, prescribed by the main European Standards, considerably reduces the possible decrease of discharge capacity or possible variation in the opening or closing behavior, due to the presence of piping.
- Metallic construction. The body and knob, in copper alloy, are particularly strong. This guarantees the maximum safety in the case of damage from accidental breakage