

RSB22200600

Brugman Type 22 2000mm x 600mm 3193W



## Technical Specification

Material: Steel  
 Finishing: Top grille and side panels  
 Valve: The valve insert (without thermostatic valve) is compatible with thermostatic valves M30 x 1,5  
 J-bracket set: blind plug, air vent, plugs  
 VDI-compliant in conformity with VDI 6036 (class III)  
 Connections: 2 x 3/4" external thread euroconus right bottom connection, 4 x 1/2" internal thread side connections  
 Packaging: Each radiator is robustly packaged in high-quality cardboard and then shrink-wrapped.  
 Painting process: All radiators are degreased, phosphated, cathodically primed and powder-coated  
 Colour: RAL 9016  
 Maximum operating pressure: 10 bar (tested at 13 bar)  
 Maximum operating temperature: 120 °C  
 Conformity: In accordance with EN442-1: 2014: radiators and convectors



## Application

The Brugman Type 22 2000mm x 600mm 3193W is used in heating systems to deliver radiant heating energy and is installed mostly at point of delivery.

## Warranty

[Download the latest warranty statement](#)

## Features

Strong and durable, steel panel radiators are a good choice for a family home or commercial space.  
 2000mm high x 600mm wide x 102mm deep  
 3193 watts calculated with 85°C flow, 75°C return  
 Multi-port options for side or bottom entry valves  
 Presented in a top coat of RAL 9010 epoxy-powder paint  
 Maximum operating pressure 10bar, maximum operating temperature 120°C  
 Well packaged with thick cardboard top and bottom caps then shrink wrapped in a tough polythene film  
 Supplied with wall mounting J brackets, air vent and port plugs