

COMBO20A

Caleffi Type A 20mm Combo Set



Technical Specification

Tempering Valve:

Recommended working pressure (dynamic) 500kPa (balanced)

Union connector with o-ring seal and cold check valve only

Temperature range adjustable 30 - 55°C

Temperature control +/- 3°C

Max. inlet temperature 85°C

Min flow rate 4L/min

Pressure Reducing Valve:

20mm female connections

Maximum inlet pressure: 2000kPa

Downstream pressure setting range: 100 – 600kPa

Factory setting: 500kPa

Maximum working temperature: 80°C

Safety Relief Valve:

15mm inlet x 15mm outlet

Male/female connections

800kPa

Temperature range: 5–110°C

Body - brass EN 12165 CW617N



Application

The Caleffi Type A 20mm Combo Set is used in plumbing systems to control, temperature, pressure and safety functions and is installed mostly in hot water cylinder cupboards.

Warranty

[Download the latest warranty statement](#)

Features

Type A reversible left or right entry manifold

20mm connections

Caleffi 5213 tempering valve with cold check

Caleffi 5335 pressure reducing valve and strainer

Caleffi 312 safety relief expansion valve with SS seat

20mm Airaga female/male ball valve

Integrated cylinder isolator and check valve

Inlet manifold features:

The manifold inlet and cold water expansion adaptors can be swapped left to right to provide either left or right hand entry to the manifold. The adaptors use o-ring seals and so do not require thread tape or similar.