



Product Name
Caleffi Connect

Product Category
General Plumbing

SKU Code
COMBO20LLP



TECHNICAL SPECIFICATION

Tempering Valve:

- Cold union connector with cold check valve
- Temperature range adjustable 30 - 50°C
- Temperature control +/- 3°C
- Max. inlet temperature 85°C
- Recommended working pressure (dynamic) 500kPa (balanced)
- Min flow rate 4L/min

APPLICATION

The Caleffi Connect Combo Set is used in plumbing systems to control, temperature, pressure and safety functions and is installed mostly in hot water cylinder cupboards.

WARRANTY

Download the latest warranty statement

HOT WATER CYLINDER KIT

Express Tail with check valve, cold water expansion valve and port:

- 800kpa cold water expansion valve
- Supports mixed flow rate up to 30L per minute

Express 4 port Manifold:

- Tank connection with isolation valve
- Inlet mains connection with check valve
- Drain port outlet (cap or ball-valve purchased separately)

Optional Pressure Reducing Valve:

- 20mm female connections
- Maximum inlet pressure: 2000kPa
- Downstream pressure setting: 100 - 600kPa
- Factory setting: 500kPa
- Maximum working temperature: 80°C
- With gauge port

FEATURES

- Faster installs - Pre-assembled and compact.
- **Meets NZ G12 low lead requirements**
- Reliable performance - backed by Caleffi engineering.
- Professional finish - Clean, consistent, and easy to maintain.