

WMGSDP20C

BMETERS 20mm Pulse Cold Meter



Technical Specification

Low lead DZR CW511L brass body

1L/Pulse

Below specifications measured at R100H↑:

Overload Flow Rate Q_{max} : 5m³/h

Permanent Flow Rate Q_3 : 4m³/h

Transitional flow rate $\pm 2\%$: 64l/h

Min flow rate $\pm 5\%$: 40l/h

Min reading: 0.05l

Max reading: 99.999m³

Max admissible pressure MAP: 16bar



The meter can be installed with horizontal flow with the dial on the top, or on the side, or vertical with upwards or downwards flow. Horizontal installation with dial downward is prohibited.

The device should be protected against frost, direct sunlight and installed in dry place. Occasional external water jets and submersion are tolerated.

Application

The BMETERS 20mm Pulse Cold Meter is used in plumbing systems to measure water quantity and is installed mostly in plant rooms.

Warranty

[Download the latest warranty statement](#)


Features

20mm pulse, single jet, dry dial, direct reading cold water up to 30°C

Pulse output via integrated REED sensor

Magnetic transmission

Complete with 20mm connection tails



Calibro Size	mm	in
L	mm	130
I	mm	228
H	mm	73
h	mm	18
B	mm	85
d	mm	1"
Peso Weight	con raccordi with unions	kg
	senza raccordi without unions	kg

Installation position			
R 100H↑	R 50H→	R 50V	R 50H↓

waterware.co.nz

Technicalteam@waterware.co.nz

0800 WATERWARE

WATERWARE